

我們從事的專業
一切皆與膜技術相關
全新一代膜技術淨化過濾器系統

www.jingyuan.hk

JINGYUAN.hk
Membrane Filter System
Filtration, Purification & Separation Solutions

MICROPOROUS MEMBRANE MATERIALS

晶元®
膜过滤器系统

New Generation Membrane Separation Refined Filtration System

风能发电机齿轮箱换油设备

Gear Oil Exchange System

技术参数 :

齿轮油输送高度 : > 100m **Gear Oil Delivery Height: >100m**

输送粘度 : 288~352(40°C运动粘度,mm²/s) **Delivery Viscosity:288~352**

高压输油管 : 100m **High Pressure Oil Delivery Pipe:100m**

残油率 : <3% **Residual Oil Rate: <3%**

换油效率 : < 3小时更换一台风机(3名工人) **Oil Exchange Efficiency:< less than 3 hours**

具有低功耗润滑油加热功能



风能发电机齿轮箱加换油设备

JY-F35

风能发电机齿轮箱加换油设备

Gear Oil Exchange System



Wind power oil exchange must choose the field refueling equipment

JY-F35



Filter Technology Solutions Partner

主要特点/FEATURES

This refueling equipment overcomes the time consuming, the cost of labor and resources, low efficiency and other deficiency of traditional oil exchange technology, Provide a simple, efficient and practical gear oil exchange system for wind power generation unit



Jingyuan has a one-stop product development and production system from the development of membrane materials to finished products To provide users with satisfactory dedicated filters and their systems

MICROPOROUS MEMBRANE MATERIALS (膜型号及规格)

| Membrane filter order models | Nominal Pore Size |
|------------------------------|-------------------|
| J22-330 L/H | 0.5~15 μ m |
| J22-400 L/H | 0.5~25 μ m |
| J30-970 L/H | |
| J30-980 L/H | |



晶元滤膜(沈阳)有限公司
SHENYANG JINGYUAN MEMBRANE SYSTEMS CO.,LTD.

www.jingyuan.hk

info@jingyuan.hk

工厂地址: 辽宁省铁岭懿路工业园区桃李沟路19号

电话: 024-78715999 139 0405 2025

