


我們從事的專業  
一切皆與膜技術相關  
全新一代膜技術淨化過濾系統

[www.jingyuan.hk](http://www.jingyuan.hk)

Membrane Filter System  
**JINGYUAN.hk**  
Filtration, Purification & Separation Solutions

晶元®  
Advanced Membrane Material  
Lube Oil Filtration



**JY-H180**

工业油品净化过滤器

Oil Filtration System



Excellent filtration effect  
The must choose refueling equipment for machinery



# MICROPOROUS MEMBRANE MATERIALS

晶元®  
膜过滤器系统

## New Generation Membrane Separation Refined Filtration System

型号 Model Type : JY-H180

流量 Flow Rate : 50~80L/min

(According to viscosity and temperature)

过滤精度 Precision : 2~10 μm (Adjustable)

过滤材料 Filtration Material : Polymer Membrane

(Can be used repeatedly after washed)

工作压力 Working Pressure : 0.2~0.3Mpa

工作温度 Temperature Range : -10°C~70°C

适用油品 Suitable Oil : Hydraulic oil, engine oil

(Petroleum or Mineral Base Oil)

电源 Voltage : 380V(Continuous Work for long time)

Equipped with an 80L oil storage tank

尺寸 Measurement : 1200×720×890mm

重量 Weight : 160Kg



**JY-H180**

## Filter Technology Solutions Partner

### 主要特点/FEATURES

Can effectively intercept and separate impurities, colloid, water and micro impurity particles in oil  
Break the emulsified structure, the oil becomes clear and transparent after filtration,

and the service life of oil is greatly improved

Comply with the national environmental protection regulations, no pollution consumables,  
no oil consumption, no need to clear sand and slag

The polymer membrane filter elements can be used repeatedly after blowing,  
save the cost of consumables

The equipment operation is simple, and there is a professional after-sales team tracking service,  
let you have no worries

Be suitable for industrial and mining enterprises, construction machinery maintenance and repair,  
and other places need oil filtration

Jingyuan has a one-stop product development and production system from the development of membrane materials to finished products  
To provide users with satisfactory dedicated filters and their systems

### MICROPOROUS MEMBRANE MATERIALS (膜型号及规格)

Membrane filter order models	Nominal Pore Size
J22-330 L/H	0.5~15 μm
J22-400 L/H	
J30-970 L/H	0.5~25 μm
J30-980 L/H	

[www.jingyuan.hk](http://www.jingyuan.hk)

[info@jingyuan.hk](mailto:info@jingyuan.hk)

晶元濾膜(沈陽)有限公司  
SHENYANG JINGYUAN MEMBRANE SYSTEMS CO.,LTD.

工厂地址: 辽宁省铁岭懿路工业园区桃李沟路19号  
电话: 024-78715999 139 0405 2025

