

我們從事的專業
一切皆與膜技術相關
全新一代膜技術淨化過濾器系統

www.jingyuan.hk

JINGYUAN.hk
Membrane Filter System
Filtration, Purification & Separation Solutions



晶元®
Advanced Membrane Material
Industrial Oil Filtration

JY-H130

工业油品净化过滤器

Oil Filtration System



Filter Technology Solutions Partner

主要特点/FEATURES

Can effectively intercept and separate impurities, colloid, water and micro impurity particles in oil
Break the emulsified structure, the oil becomes clear and transparent after filtration, and the service life of oil is greatly improved
Comply with the national environmental protection regulations, no pollution consumables, no oil consumption, no need to clear sand and slag
The polymer membrane filter elements can be used repeatedly after blowing, save the cost of consumables
The equipment operation is simple, and there is a professional after-sales team tracking service, let you have no worries
Be suitable for hydraulic oil, engine oil, lube oil, gear oil and other industrial oil



Excellent filtration effect

The must choose refueling equipment for construction machinery

MICROPOROUS MEMBRANE MATERIALS

晶元®
膜过滤器系统

New Generation Membrane Separation Refined Filtration System

型号 Model Type : JY-H130

流量 Flow Rate : 15~30L/min

(According to viscosity and temperature)

过滤精度 Precision : 2~10 μm (Adjustable)

过滤材料 Filtration Material : Polymer Membrane

(Can be used repeatedly after washed)

工作压力 Working Pressure : 0.2~0.3Mpa

过滤级数 Filtration Classification: Three

(Pre-filtration/Magnetic Filtration/Refined Filtration)

工作温度 Temperature Range : -10°C~70°C

适用油品 Suitable Oil : Hydraulic oil, engine oil, gear oil

(Petroleum or Mineral Base Oil)

电源 Voltage : 380V(Continuous Work for long time)

尺寸 Measurement : 450×700×890mm

重量 Weight : 82kg



JY-H130

Filter Technology Solutions Partner

主要特点/FEATURES

Can effectively intercept and separate impurities, colloid, water and micro impurity particles in oil
Break the emulsified structure, the oil becomes clear and transparent after filtration, and the service life of oil is greatly improved
Comply with the national environmental protection regulations, no pollution consumables, no oil consumption, no need to clear sand and slag
The polymer membrane filter elements can be used repeatedly after blowing, save the cost of consumables
The equipment operation is simple, and there is a professional after-sales team tracking service, let you have no worries
Be suitable for hydraulic oil, engine oil, lube oil, gear oil and other industrial oil

Jingyuan has a one-stop product development and production system from the development of membrane materials to finished products
To provide users with satisfactory dedicated filters and their systems

MICROPOROUS MEMBRANE MATERIALS (膜型号及規格)

Membrane filter order models	Nominal Pore Size
J22-330 L/H	0.5~15 μ m
J22-400 L/H	
J30-970 L/H	0.5~25 μ m
J30-980 L/H	

www.jingyuan.hk

info@jingyuan.hk

工厂地址：辽宁省铁岭懿路工业园区桃李沟路19号

电话：024-78715999 139 0405 2025



晶元滤膜(沈阳)有限公司

SHENYANG JINGYUAN MEMBRANE SYSTEMS CO.,LTD.

