

我們從事的專業  
一切皆與膜技術相關  
全新一代膜技術淨化過濾器系統

[www.jingyuan.hk](http://www.jingyuan.hk)

**JINGYUAN.hk**  
Membrane Filter System  
Filtration, Purification & Separation Solutions

# MICROPOROUS MEMBRANE MATERIALS

Diesel Fuel Filtration

晶元®

膜過濾器系統

New Generation Membrane Separation Refined Filtration System (Large-scale Filtration System)

型号 Model : JY-DL60

流量 Flow Rate (According to oil quality): 60~80m<sup>3</sup>/h

过滤精度 Precision: 2~15μm (可根据系统要求选择)

过滤材料 Filtering Material: 晶元高分子膜材料

工作压力 Working Pressure: 0.2 ~ 0.3Mpa

预过滤器 Pre-filtration: Y

进出油管径 Oil inlet and oil outlet: DN100 (4')

适用油品 Apply to oil: 轻质柴油、航空煤油、汽油(定制)、其他液体 (定制)

尺寸 Measurement: 6850×1700×2400mm

注 Remark: 流量随油品质量、粘度、设备维护等指标有所变化，并非绝对值

# JY=D<sub>L</sub>60



## 主要特点/FEATURES

Effectively intercept impurities, colloid and water in oil

The cleanliness level is greatly improved after filtration

Effectively extending the service life of mechanical equipment

Comply with the national environmental protection regulations, no pollution consumables, no diesel consumption, no need to clear sand and slag

The polymer membrane filter elements can be used repeatedly after blowing, save the cost of consumables

The equipment operation is simple, and there is a professional after-sales team tracking service, let you have no worries

Widely being used in oil refined filtration(oil depot, oil refinery, gas station and so on)



炼油厂应用

Jingyuan has a one-stop product development and production system from the development of membrane materials to finished products To provide users with satisfactory dedicated filters and their system

## MICROPOROUS MEMBRANE MATERIALS (膜型号及規格)

Membrane filter order models	Nominal Pore Size
J22-330 L/H	0.5~15 μ m
J22-400 L/H	
J30-970 L/H	0.5~25 μ m
J30-980 L/H	



晶元滤膜(沈阳)有限公司

SHENYANG JINGYUAN MEMBRANE SYSTEMS CO.,LTD.

[www.jingyuan.hk](http://www.jingyuan.hk)

[info@jingyuan.hk](mailto:info@jingyuan.hk)

工厂地址：辽宁省铁岭懿路工业园区桃李沟路19号

电话：024-78715999 139 0405 2025

